

## Microflex PE-X S Coupling

### Description

Microflex straight coupling for sanitary pipe PE-Xa (PN10 - SDR 7.4)

Straight coupling for use in piping systems equipped with transport pipes for sanitary, cold or hot water applications.

The coupling has a long supporting pipe for optimal clamping, a cylindrical outside tread and a clamping ring with stainless steel bolt. The included remote plate makes it easier to fit the coupling. Using different threaded fittings the couplings can be combined to elbows, tees and other ancillary connections.

Using these couplings, fitted and tightened according the manual and the designated moments of force, guarantees an optimal clamping.

### Technical specifications

Type	∅ ext. PE-Xa/PE <i>mm</i>	∅ int. PE-Xa/PE <i>mm</i>	Thread <i>inch</i>	M/F	Size bolt	Weight <i>kg</i>
<b>MJ3413420/28</b>	20	15	3/4"	M	M6	0,17
<b>MJ3413425/35</b>	25	20	3/4"	M	M6	0,22
<b>MJ3414432/44</b>	32	25	1"	M	M6	0,33
<b>MJ3415440/55</b>	40	32	1 1/4"	M	M8	0,60
<b>MJ3416450/69</b>	50	40	1 1/2"	M	M10	0,82
<b>MJ341263/87</b>	63	50	2"	M	M12	1,46

Supporting pipe material: CW617N

Clamping ring material: CW602N

Temperature/Pressure: 95°C/10 bar

### Manufacturer

Watts Insulation NV  
 Nieuwlandlaan B321  
 B - 3200 Aarschot

Tel.: +32 16 44 21 31

Fax: +32 16 44 03 68

E-mail: sales@wattsinsulation.com